

33
triisostearate and an ester formed by the reaction of trimethylolpropane and a mixture of C₅-C₉ straight chain saturated monocarboxylic acids, in a weight ratio of about 1.2:1.0, and about 15% of said additive, said percentages being based on the weight of said composition.

34
30. (Amended) A biodegradable two-cycle engine oil composition, as claimed in claim 29, [including an ashless] wherein said additive is selected from the group consisting of a polyamide, a alkenylsuccinimide, a boric acid-modified alkenylsuccinimide, a phenolic amine, a succinate derivative or a combination of any two or more of said additives.

35
31. (Amended) A biodegradable two-cycle engine oil composition, as claimed in claim 29, [including an ashless] wherein said additive is selected from the group consisting of sulfonate phosphonate, an alkaline earth metal, phenate, or a combination of any two or more of said additives.

REMARKS

Claims 11-12, 14-16, 20, and 30-31 have been amended to overcome informalities as was done in an Amendment filed on or about August 8, 1994 in grandparent application Serial No. 08/119,318, filed September 9, 1993.

13. A biodegradable two-cycle engine oil composition comprising:

(A) an ester base stock consisting essentially of a blend of (a) a first polyolester comprising, as its reactive components, a neopentylpolyol and a C_{16} - C_{20} branched chain saturated monocarboxylic acid and (b) a second polyol ester comprising, as its reactive components, a neopentylpolyol and a carboxylic acid selected from the group consisting of at least one C_5 - C_{10} straight chain, saturated monocarboxylic acid or at least one C_{16} - C_{20} straight or branched chain, unsaturated monocarboxylic acids; and, optionally, a relatively low molecular weight ester comprising, as its reactive components, a C_8 - C_{13} straight or branched chain monohydric alcohol and a C_5 - C_{12} straight or branched chain carboxylic acid, said ester base stock having the following characteristics:

- (i) biodegradability of $\geq 80\%$, as determined by CEC-L-33-T-82;
- (ii) flash point of $\geq 175^\circ\text{C}$; and
- (iii) kinematic viscosity of less than 15 cSt at 100°C ; and

(B) a detergent/dispersant additive, said composition having the following characteristics:

- (i) biodegradability of $\geq 80\%$, as determined by CEC-L-33-T-82;
- (ii) flash point of $\geq 175^\circ\text{C}$;
- (iii) kinematic viscosity of less than 15 cSt at 100°C ; and
- (iv) miscibility with gasoline, in a fuel/oil ratio of 16:1 to 100:1, of $\leq 110\%$ of reference oil, as determined by ASTM-4682, using Citgo-93738 as said reference oil for category 3, according to SAE J1536.

SUB
B2

14. A biodegradable two-cycle engine oil composition, as claimed in claim 13, including an ashless additive selected from the group consisting of a polyamide, a alkenylsuccinimide, a boric acid-modified alkenylsuccinimide, a phenolic amine, a succinate derivative or a combination of any two or more of said additives.

15. A biodegradable two-cycle engine oil composition, as claimed in claim 13, including an ash-containing additive selected from the group consisting of sulfonate phosphonate, an alkaline earth metal, phenate, or a combination of any two or more of said additives.

16. A biodegradable two-cycle engine oil composition as claimed in claim 13, comprising from about 80% to about 90% of said ester base stock and from about 10% to about 20% of said performance additive, based on the weight of said composition.

17. A biodegradable two-cycle engine oil composition, as claimed in claim 14, comprising about 85% of an ester base stock, consisting essentially of a blend of trimethylolpropane triisostearate and trimethylolpropane tripelargonate in a weight ratio of about 0.7:1.0, and about 15% of said additive, said percentages being based on the weight of said composition.

18. A biodegradable two-cycle engine oil composition, as claimed in claim 14, comprising about 85% of an ester base stock consisting essentially of a blend of trimethylolpropane triisostearate and an ester comprising, as its reactive components, trimethylolpropane and a mixture of caprylic acid and

19. A biodegradable two-cycle engine oil composition, as claimed in claim 14, comprising about 85% of an ester base stock consisting essentially of trimethylolpropane triisostearate and trimethylolpropane trioleate in a weight ratio of about 3.0:1.0, and about 15% of said additive, said percentages being based on the weight of said composition.

21. An ester base stock for a two-cycle engine oil composition, said base stock consisting essentially of a blend of (a) a first polyol ester comprising, as its reactive components, a neopentylpolyol and a C₈-C₁₀ straight chain, saturated monocarboxylic acid and (b) a second complex polyol ester comprising, as its reactive components, a neopentylpolyol, a C₆-C₁₂ dicarboxylic acid and a C₅-C₁₀ straight or branched chain, saturated monocarboxylic acid; and, optionally, a relatively low molecular weight ester comprising, as its reactive components, a C₈-C₁₃ straight or branched chain monohydric alcohol and a C₅-C₁₂ straight or branched

chain carboxylic acid, said ester base stock having the following characteristics:

- (i) biodegradability of $\geq 80\%$, as determined by CEC-L-33-T-82;
- (ii) flash point of $\geq 175^{\circ}\text{C}$; and
- (iii) kinematic viscosity of less than 15 cSt at 100°C .

22. An ester base stock as claimed in claim 21, wherein the neopentylpolyol component of said first and said second ester is selected from the group consisting of trimethylolpropane, pentaerythritol, ditrimethylolpropane, dipentaerythritol, neopentylglycol, trimethylolethane and mixtures of two or more of said neopentylpolyols.

23. An ester base stock as claimed in claim 21, consisting essentially of from about 25% to about 85% of said first ester and from about 15% to about 75% of said second ester, based on the weight of said ester base stock.

24. An ester base stock as claimed in claim 23, consisting essentially of about 85% of trimethylolpropane tripelargonate and about 15% of a complex polyol ester comprising, as its reactive components, trimethylolpropane, and an acid mixture consisting essentially of caprylic acid and capric acid, and adipic acid, the weight ratio thereof being in a range from about 2.5:1.0 to 3.0:1.0, caprylic acid-capric acid to adipic acid, said percentages being based on the weight of said ester base stock.

25. An ester base stock as claimed in claim 23, consisting essentially of about 75% trimethylolpropane tripelargonate and about 25% of a

complex polyol ester comprising, as its reactive components, trimethylolpropane, and an acid mixture consisting essentially of caprylic acid and capric acid, and adipic acid, the weight ratio thereof being in a range from about 2.5:1.0 to 3.0:1.0, caprylic acid-capric acid to adipic acid, said percentages being based on the weight of said ester base stock.

26. An ester base stock as claimed in claim 23, consisting essentially of about 70% trimethylolpropane tripelargonate and about 30% of a complex polyol ester comprising, as its reactive components, trimethylolpropane, and an acid mixture consisting essentially of caprylic acid and capric acid, and adipic acid, the weight ratio thereof being in a range from about 2.5:1.0 to 3.0:1.0, caprylic acid-capric acid to adipic acid, said percentages being based on the weight of said ester base stock.

27. An ester base stock as claimed in claim 23, consisting essentially of about 55% trimethylolpropane tripelargonate and about 45% of a complex polyol ester comprising, as its reactive components, trimethylolpropane, and an acid mixture consisting essentially of caprylic acid and capric acid, and adipic acid, the weight ratio thereof being in a range from about 2.5:1.0 to 3.0:1.0, caprylic acid-capric acid to adipic acid, said percentages being based on the weight of said ester base stock.

28. An ester base stock as claimed in claim 23, consisting essentially of about 45% trimethylolpropane tripelargonate and about 55% of a complex polyol ester comprising, as its reactive components, trimethylolpropane, and an acid mixture consisting essentially of caprylic acid and capric

acid, and adipic acid, the weight ratio thereof being in a range from about 2.5:1.0 to 3.0:1.0, caprylic acid-capric acid to adipic acid, said percentages being based on the weight of said ester base stock.

(21)^{same} 29. A biodegradable two-cycle engine oil composition comprising:

(A) an ester base stock consisting essentially of a blend of (a) a first polyol ester, comprising, as its reactive components, a neopentylpolyol and a C₈-C₁₀ straight chain, saturated monocarboxylic acid and (b) a second complex polyol ester comprising, as its reactive components, a neopentylpolyol, a C₆-C₁₂ dicarboxylic acid and a C₅-C₁₀ straight or branched chain, saturated monocarboxylic acid; and, optionally, a relatively low molecular weight ester comprising, as its reactive components, a C₈-C₁₃ straight or branched chain monohydric alcohol and a C₅-C₁₂ straight or branched chain carboxylic acid, said ester base stock having the following characteristics:

- (i) biodegradability of $\geq 80\%$, as determined by CEC-L-33-T-82;
- (ii) flash point of $\geq 175^{\circ}\text{C}$; and
- (iii) kinematic viscosity of less than 15 cSt at 100°C ; and

(B) a detergent/dispersant additive, said composition having the following characteristics:

- (i) biodegradability of $\geq 80\%$, as determined by CEC-L-33-T-82;
- (ii) flash point of $\geq 175^{\circ}\text{C}$;
- (iii) kinematic viscosity of less than 15 cSt at 100°C ; and
- (iv) miscibility with gasoline, in a fuel/oil ratio of 16:1 to 100:1, of $\leq 110\%$ of reference oil, as determined by ASTM-4682, using

Citgo-93738 as said reference oil for category 3, according to SAE J1536.

506
64

~~30. A biodegradable two-cycle engine oil composition, as claimed in claim 29, including an ashless additive selected from the group consisting of a polyamide, an alkenylsuccinimide, a boric acid-modified alkenylsuccinimide, a phenolic amine, a succinate derivative or a combination of any two or more of said additives.~~

31. A biodegradable two-cycle engine oil composition, as claimed in claim 29, including an ash-containing additive selected from the group consisting of sulfonate, an alkaline earth metal, phosphonate, phenate, or a combination of any two or more of said additives.

32. A biodegradable two-cycle engine oil composition as claimed in claim 29 comprising from about 80% to about 90% of said ester base stock and from about 10% to about 20% of said additive, based on the weight of said composition.

33. A biodegradable two-cycle engine oil composition, as claimed in claim 30¹¹², comprising about 85% of an ester base stock consisting essentially of a blend of trimethylolpropane tripelargonate and a complex polyol ester comprising, as its reactive components, trimethylolpropane and an acid mixture consisting essentially of caprylic acid and capric acid, and adipic acid, the weight ratio of acid components of said complex ester being in a range from about 2.5:1.0 to 3.0:1.0 caprylic acid-capric acid to adipic acid, and the weight ratio of simple to complex esters in said blend being about 1.0:0.18, and about

34. A biodegradable two-cycle engine oil composition, as claimed in claim 30¹¹², comprising about 85% of an ester base stock consisting essentially of a blend of trimethylolpropane tripelargonate and a complex polyol ester comprising, as its reactive components, trimethylolpropane and an acid mixture consisting essentially of caprylic acid and capric acid, and adipic acid, the weight ratio of acid components of said complex ester being in a range from about 2.5:1.0 to 3.0:1.0 caprylic acid-capric acid to adipic acid, and the weight ratio of simple to complex esters in said blend being about 1.0:0.35, and about 15% of said additive, said percentages being based on the weight of said composition.

35. A biodegradable two-cycle engine oil composition, as claimed in claim 30¹¹², comprising about 85% of an ester base stock consisting essentially of a blend of trimethylolpropane tripelargonate and a complex polyol ester comprising, as its reactive components, trimethylolpropane and an acid mixture consisting essentially of caprylic acid and capric acid, and adipic acid, the weight ratio of acid components of said complex ester being in a range from about 2.5:1.0 to 3.0:1.0 caprylic acid-capric acid to adipic acid, and the weight ratio of simple to complex esters in said blend being about 1.0:0.45, and about 15% of said additive, said percentages being based on the weight of said composition.

36. A biodegradable two-cycle engine oil composition, as claimed in claim 30, comprising about 85% of an ester base stock consisting essentially of a

blend of trimethylolpropane tripelargonate and a complex polyol ester comprising, as its reactive components, trimethylolpropane and an acid mixture consisting essentially of caprylic acid and capric acid, and adipic acid, the weight ratio of acid components of said complex ester being in a range from about 2.5:1.0 to 3.0:1.0 caprylic acid-capric acid to adipic acid, and the weight ratio of simple to complex esters in said blend being about 1.0:0.80, and about 15% of said additive, said percentages being based on the weight of said composition.

37. A biodegradable two-cycle engine oil composition, as claimed in claim 30, comprising about 85% of an ester base stock consisting essentially of a blend of trimethylolpropane tripelargonate and a complex polyol ester comprising, as its reactive components, trimethylolpropane and an acid mixture consisting essentially of caprylic acid and capric acid, and adipic acid, the weight ratio of acid components of said complex ester being in a range from about 2.5:1.0 to 3.0:1.0 caprylic acid-capric acid to adipic acid, and the weight ratio of simple to complex esters in said blend being about 1.0:1.2, and about 15% of said additive, said percentages being based on the weight of said composition.

38. A method of lubricating a two-cycle engine which comprises bringing the components of said engine which are to be lubricated into contact with an effective amount of the composition of claim 13.

39. A method of lubricating a two-cycle engine which comprises bringing the components of said engine which are to be lubricated into contact with an effective amount of the composition of claim 29.

40. A method as claimed in claim 38, wherein said engine is lubricated with a composition comprising about 85% of an ester base stock consisting essentially of a blend of trimethylolpropane triisostearate and trimethylolpropane tripelargonate, in a weight ratio of about 0.7:1.0, and about 15% of an ashless detergent/dispersant additive selected from the group consisting of a polyamide, an alkenylsuccinimide, a boric acid-modified alkenylsuccinimide, a phenolic amine, a succinate derivative, or a combination of any two or more of said additives, said percentages being based on the weight of said composition.

41. A method as claimed in claim 39, wherein said engine is lubricated with a composition comprising about 85% of an ester base stock consisting essentially of a blend of trimethylolpropane triisostearate and trimethylolpropane tripelargonate, in a weight ratio of about 0.7:1.0, and about 15% of an ashless detergent/dispersant additive selected from the group consisting of a polyamide, an alkenylsuccinimide, a boric acid-modified alkenylsuccinimide, a phenolic amine, a succinate derivative, or a combination of any two or more of said additives, said percentages being based on the weight of said composition.

2025-11-13 14:30:33